




Biological safety cabinet

Description	Image																								
<p>BIOLOGICAL SAFETY CABINET, Class II, Type B: (Digital) Biological safety cabinet (Class II) provides operator and product protection for work.</p> <ul style="list-style-type: none">• Operator and product protection• Exhaust through HEPA Filter• Recirculating exhaust options• No Re-circulation 100% air Exhausted Through HEPA Filter• Safety parameters constantly monitored• Fan, Light, UV, outlet, silence, power (ON/OFF) digital keypad• Slash up/down press button																									
<table border="1"><tbody><tr><td data-bbox="99 831 435 968">Dimensions: Working zone</td><td data-bbox="435 831 1032 968">L 4.8' xD2.8' x H7'</td></tr><tr><td data-bbox="99 968 435 1024">Glass working height:</td><td data-bbox="435 968 1032 1024">200mm</td></tr><tr><td data-bbox="99 1024 435 1100">Front screen:</td><td data-bbox="435 1024 1032 1100">Sash Glass with counter balance up down press button</td></tr><tr><td data-bbox="99 1100 435 1157">Inner liner:</td><td data-bbox="435 1100 1032 1157">Crevice free 304 stainless steel</td></tr><tr><td data-bbox="99 1157 435 1192">Work area:</td><td data-bbox="435 1157 1032 1192">Recessed 304 stainless steel tray</td></tr><tr><td data-bbox="99 1192 435 1249">Construction:</td><td data-bbox="435 1192 1032 1249">Mild steel with powder coating</td></tr><tr><td data-bbox="99 1249 435 1285">Noise level:</td><td data-bbox="435 1249 1032 1285"><65 dBA at 1m</td></tr><tr><td data-bbox="99 1285 435 1341">Lighting:</td><td data-bbox="435 1285 1032 1341">800-1000 lux at work surface</td></tr><tr><td data-bbox="99 1341 435 1377">Filters:</td><td data-bbox="435 1341 1032 1377">H-14, 99.999% HEPA</td></tr><tr><td data-bbox="99 1377 435 1453">Electrical supply:</td><td data-bbox="435 1377 1032 1453">230v / 50Hz single phase (other voltages available)</td></tr><tr><td data-bbox="99 1453 435 1488">Portable UV – UV socket</td><td data-bbox="435 1453 1032 1488">Double electric socket</td></tr><tr><td data-bbox="99 1488 435 1528">Stand</td><td data-bbox="435 1488 1032 1528">caster</td></tr></tbody></table>	Dimensions: Working zone	L 4.8' xD2.8' x H7'	Glass working height:	200mm	Front screen:	Sash Glass with counter balance up down press button	Inner liner:	Crevice free 304 stainless steel	Work area:	Recessed 304 stainless steel tray	Construction:	Mild steel with powder coating	Noise level:	<65 dBA at 1m	Lighting:	800-1000 lux at work surface	Filters:	H-14, 99.999% HEPA	Electrical supply:	230v / 50Hz single phase (other voltages available)	Portable UV – UV socket	Double electric socket	Stand	caster	
Dimensions: Working zone	L 4.8' xD2.8' x H7'																								
Glass working height:	200mm																								
Front screen:	Sash Glass with counter balance up down press button																								
Inner liner:	Crevice free 304 stainless steel																								
Work area:	Recessed 304 stainless steel tray																								
Construction:	Mild steel with powder coating																								
Noise level:	<65 dBA at 1m																								
Lighting:	800-1000 lux at work surface																								
Filters:	H-14, 99.999% HEPA																								
Electrical supply:	230v / 50Hz single phase (other voltages available)																								
Portable UV – UV socket	Double electric socket																								
Stand	caster																								
Make: , Technocratic , Pakistan																									

Summaiya Altaf

03003972448