



TECHNOCRATIC SERVICES

ISO 9001:2015 Certified Company




PORTABLE ULTRASONIC HUMIDIFIER

Description	Image														
<p>Product Description:</p> <ol style="list-style-type: none"> 1. Adopting integrated mist module inside: the chip is replaceable and the machine is easy to maintain. 2. Boasting high humidification efficiency: diameter of fog output is only1-10u. Maximum relative humidity reaches 99%. 3. Adopting waterproof fan & waterproof transformers to prevent short circuits, keeping machine long service life. 4. Intelligent control, accurate humidity control: humidity control system with imported world leading probe. The range of humidity control is 1%RH~90%RH 5. Timing humidification: customers can control the humidifier turned on or off according to the time required. 6. Pure water bucket connectable: customer can use the pure water bucket to solve the troubles of connecting a water pipe. 7. Easy to move, convenient to install. It is able to move and to be mounted on external wall. Both automatic and manual humidify control are available. It depends on you. 8. Stainless steel body: clean ,reliable,durable and long service life. 9. Equipped with standard water feeding gap, water release switch, overflow gap etc. The water feeding gap will fill water automatically. 10. Improving the indoor environment: humidifying & eliminating dust and it also create high concentration of negative oxygen ions which can increase employee productivity and help enhance and improve people's mental healthy, emotional healthy, thinking, and memory, etc. <p>Warm tips:</p> <ol style="list-style-type: none"> 1.Environment Temperature: -1~40°C 2.Water Supply Pressure: 1-4KG/CM2 3.Environment Humidity: ≤ 99%RH 4.Water Supply Temperature: 1-45°C(30°Cwill be best) 5.Water Supply Quality: softened water,pure water,tap water 6.Using Environment: no high temperature radiation source, nor strong magnetic field interference 															
<p>Technical Specifications:</p> <table border="1"> <tr> <td>Capacity</td> <td>2KG/h</td> </tr> <tr> <td>Rated Voltage</td> <td>220V-50Hz</td> </tr> <tr> <td>Rated power</td> <td>200W</td> </tr> <tr> <td>Control</td> <td>Manual</td> </tr> <tr> <td>Application area</td> <td>10-40 m²</td> </tr> <tr> <td>Size</td> <td>710X360X400mm</td> </tr> <tr> <td>NW</td> <td>19.5kg</td> </tr> </table>	Capacity	2KG/h	Rated Voltage	220V-50Hz	Rated power	200W	Control	Manual	Application area	10-40 m ²	Size	710X360X400mm	NW	19.5kg	<p>2KG/h</p> 
Capacity	2KG/h														
Rated Voltage	220V-50Hz														
Rated power	200W														
Control	Manual														
Application area	10-40 m ²														
Size	710X360X400mm														
NW	19.5kg														



TECHNOCRATIC SERVICES

ISO 9001:2015 Certified Company

<table border="1"> <tbody> <tr> <td>Capacity</td> <td>3KG/h</td> </tr> <tr> <td>Rated Voltage</td> <td>220V-50Hz</td> </tr> <tr> <td>Rated power</td> <td>300W</td> </tr> <tr> <td>Control</td> <td>Manual</td> </tr> <tr> <td>Application area</td> <td>30-60 m²</td> </tr> <tr> <td>Size</td> <td>710X360X400mm</td> </tr> <tr> <td>NW</td> <td>21.5 kg</td> </tr> </tbody> </table>	Capacity	3KG/h	Rated Voltage	220V-50Hz	Rated power	300W	Control	Manual	Application area	30-60 m ²	Size	710X360X400mm	NW	21.5 kg	<p style="text-align: center;">3KG/h</p> 												
Capacity	3KG/h																										
Rated Voltage	220V-50Hz																										
Rated power	300W																										
Control	Manual																										
Application area	30-60 m ²																										
Size	710X360X400mm																										
NW	21.5 kg																										
<table border="1"> <tbody> <tr> <td>Capacity</td> <td>6KG/h</td> </tr> <tr> <td>Rated Voltage</td> <td>220V-50Hz</td> </tr> <tr> <td>Rated power</td> <td>400W</td> </tr> <tr> <td>Control</td> <td>Manual</td> </tr> <tr> <td>Application area</td> <td>60-90 m²</td> </tr> <tr> <td>Size</td> <td>710X360X400mm</td> </tr> <tr> <td>NW</td> <td>23kg</td> </tr> </tbody> </table>	Capacity	6KG/h	Rated Voltage	220V-50Hz	Rated power	400W	Control	Manual	Application area	60-90 m ²	Size	710X360X400mm	NW	23kg	<p style="text-align: center;">6KG/h</p> 												
Capacity	6KG/h																										
Rated Voltage	220V-50Hz																										
Rated power	400W																										
Control	Manual																										
Application area	60-90 m ²																										
Size	710X360X400mm																										
NW	23kg																										
<table border="1"> <tbody> <tr> <td>Capacity</td> <td>12KG/h</td> </tr> <tr> <td>Rated Voltage</td> <td>220V-50Hz</td> </tr> <tr> <td>Rated power</td> <td>800W</td> </tr> <tr> <td>Control</td> <td>Automatically</td> </tr> <tr> <td>Atomized particle</td> <td>1-5 μm</td> </tr> <tr> <td>Amount of air flow</td> <td>110m³/hr</td> </tr> <tr> <td>Foggy outlet diameter</td> <td>110 mm*1</td> </tr> <tr> <td>Application area</td> <td>120-150 m²</td> </tr> <tr> <td>Operation humidifier RH%</td> <td>10%-90%</td> </tr> <tr> <td>Operation Temperature</td> <td>3 °C -40 °C</td> </tr> <tr> <td>Spray</td> <td>double</td> </tr> <tr> <td>Size</td> <td>760X380X400mm</td> </tr> <tr> <td>NW</td> <td>32.5kg</td> </tr> </tbody> </table>	Capacity	12KG/h	Rated Voltage	220V-50Hz	Rated power	800W	Control	Automatically	Atomized particle	1-5 μm	Amount of air flow	110m ³ /hr	Foggy outlet diameter	110 mm*1	Application area	120-150 m ²	Operation humidifier RH%	10%-90%	Operation Temperature	3 °C -40 °C	Spray	double	Size	760X380X400mm	NW	32.5kg	<p style="text-align: center;">12KG/h</p> 
Capacity	12KG/h																										
Rated Voltage	220V-50Hz																										
Rated power	800W																										
Control	Automatically																										
Atomized particle	1-5 μm																										
Amount of air flow	110m ³ /hr																										
Foggy outlet diameter	110 mm*1																										
Application area	120-150 m ²																										
Operation humidifier RH%	10%-90%																										
Operation Temperature	3 °C -40 °C																										
Spray	double																										
Size	760X380X400mm																										
NW	32.5kg																										



TECHNOCRATIC SERVICES

ISO 9001:2015 Certified Company



Please feel free to contact Erum Manzoor 0333-0297007, 0301-922881

Head Office Karachi



+92-21-35001798

+92-333-0297007



+92-321-2202241

+92-300-3972448



www.technocratics.com.pk



technoratics@gmail.com
info@technocratics.com.pk



Plot No. 763, Future Colony Mor, Main Korangi
Industrial Area Road, Karachi-75120

Branch Office Lahore



0333-0297007, 0335-4944616, 0321-2202241



Plot # 42, Street # 2, Block-C, Asim Town,
Harbanspura Underpass Near Ring Road,
Lahore-Pakistan.