




UV-VIS SPECTROPHOTOMETER

| Description | Image | | | | | | | | | | | | | | | | | | | | |
|--|---|------------|---------------------|--|--------------------------|--|---------------------------|--|-------|---|----------|--|---------------------|--|-------|---------------------------|----------------|---------------------------------------|------|------|---|
| <p>UV/Vis Spectrophotometer Single beam (computer software Spectrophotometer) Model: 752N Software optional</p> <p>Common Features</p> <ol style="list-style-type: none"> High quality silicon photometric diode detector and 1200 lines/mm diffraction grating ensure the high-quality accuracy and precision. Backlit LCD display for an easy readout. Automatic 0A and 100%T. Easy switching of transmittance, absorbance and concentration modes, just by pressing one key. Direct concentration read-out and concentration factor setting function. Large sample compartment, for 5-100mm path length cuvettes with optional holders. Easy to change the halogen lamp or deuterium lamp by the user himself. <p>Specifications:</p> <table border="1" data-bbox="172 965 930 1447"> <tr> <td>Wavelength Range</td> <td>200-1000nm</td> </tr> <tr> <td>Wavelength Accuracy</td> <td></td> </tr> <tr> <td>Wavelength Repeatability</td> <td></td> </tr> <tr> <td>Photometric Repeatability</td> <td></td> </tr> <tr> <td>Noise</td> <td>100% (T) noise≤0.3% (T) , 0% (T) noise≤0.2% (T)</td> </tr> <tr> <td>Drifting</td> <td></td> </tr> <tr> <td>Cuvette Holder Size</td> <td></td> </tr> <tr> <td>Power</td> <td>AC220V±22V 50Hz±1Hz, 120W</td> </tr> <tr> <td>Packaging Size</td> <td>640mm×480mm×340mm 0.078M³</td> </tr> <tr> <td>G.W.</td> <td>30kg</td> </tr> </table> <p>Make: China Computer and printer will be provided by the client</p> | Wavelength Range | 200-1000nm | Wavelength Accuracy | | Wavelength Repeatability | | Photometric Repeatability | | Noise | 100% (T) noise≤0.3% (T) , 0% (T) noise≤0.2% (T) | Drifting | | Cuvette Holder Size | | Power | AC220V±22V 50Hz±1Hz, 120W | Packaging Size | 640mm×480mm×340mm 0.078M ³ | G.W. | 30kg |  |
| Wavelength Range | 200-1000nm | | | | | | | | | | | | | | | | | | | | |
| Wavelength Accuracy | | | | | | | | | | | | | | | | | | | | | |
| Wavelength Repeatability | | | | | | | | | | | | | | | | | | | | | |
| Photometric Repeatability | | | | | | | | | | | | | | | | | | | | | |
| Noise | 100% (T) noise≤0.3% (T) , 0% (T) noise≤0.2% (T) | | | | | | | | | | | | | | | | | | | | |
| Drifting | | | | | | | | | | | | | | | | | | | | | |
| Cuvette Holder Size | | | | | | | | | | | | | | | | | | | | | |
| Power | AC220V±22V 50Hz±1Hz, 120W | | | | | | | | | | | | | | | | | | | | |
| Packaging Size | 640mm×480mm×340mm 0.078M ³ | | | | | | | | | | | | | | | | | | | | |
| G.W. | 30kg | | | | | | | | | | | | | | | | | | | | |

Head Office Karachi

-  +92-21-35001798
-  +92-333-0297007
-  +92-321-2202241
-  +92-300-3972448
-  www.technocratics.com.pk
-  technoratics@gmail.com
-  info@technocratics.com.pk
-  Plot No. 763, Future Colony Mor, Main Korangi Industrial Area Road, Karachi-75120

Branch Office Lahore

-  0333-0297007, 0335-4944616, 0321-2202241
-  Plot # 42, Street # 2, Block-C, Asim Town, Harbanspura Underpass Near Ring Road, Lahore-Pakistan.