




Bench Top Air Sampler for Microbiological area monitoring

Description	Image																						
<p><u>Air Sampler for Microbiological area monitoring</u> <u>Model : FKC-II</u></p> <ol style="list-style-type: none"> 1. Sampling hole has many small holes to reduce puffball superposition and reduce error of animalcule count. 2. Programmable, sampling quantity can be set from 0.01 to 2.0 steers. 3. LCD displays sampling quantity, sampling time and other parameters. 4. Save sampling quantity, sampling time and other parameters in pages and save 256 pages at most. 5. Particular sculpting, convenient to use. 6. Simple to exchange substrate utensil, just only take down sampling hole to exchange substrate utensil. (Standard diameter is 90*15.) 																							
<table border="1"> <tbody> <tr> <td>model</td> <td>FKC-2 air biological sampler</td> </tr> <tr> <td>Parameter</td> <td></td> </tr> <tr> <td>Sampling quantity</td> <td>3.53CFM/min</td> </tr> <tr> <td>Speed of sampling hole</td> <td><0.4m>/s, basically the same as that of clean room (isokinetic sampling)</td> </tr> <tr> <td>Power supply</td> <td>AC & DC, chargeable buttry: DC7.4V, continuous work for 4h after charged</td> </tr> <tr> <td>Speed crash</td> <td>16m/s</td> </tr> <tr> <td>Collection efficiency</td> <td>95%</td> </tr> <tr> <td>Sampling range</td> <td>10-6000L</td> </tr> <tr> <td>Volume</td> <td>φ120*300</td> </tr> <tr> <td>Weight</td> <td>2.5Kg</td> </tr> <tr> <td>Configuration</td> <td>AC Adapter,2Substrate Vtensil ,Instruction Manual ,Inspection report, Warranty Card</td> </tr> </tbody> </table>	model	FKC-2 air biological sampler	Parameter		Sampling quantity	3.53CFM/min	Speed of sampling hole	<0.4m>/s, basically the same as that of clean room (isokinetic sampling)	Power supply	AC & DC, chargeable buttry: DC7.4V, continuous work for 4h after charged	Speed crash	16m/s	Collection efficiency	95%	Sampling range	10-6000L	Volume	φ120*300	Weight	2.5Kg	Configuration	AC Adapter,2Substrate Vtensil ,Instruction Manual ,Inspection report, Warranty Card	
model	FKC-2 air biological sampler																						
Parameter																							
Sampling quantity	3.53CFM/min																						
Speed of sampling hole	<0.4m>/s, basically the same as that of clean room (isokinetic sampling)																						
Power supply	AC & DC, chargeable buttry: DC7.4V, continuous work for 4h after charged																						
Speed crash	16m/s																						
Collection efficiency	95%																						
Sampling range	10-6000L																						
Volume	φ120*300																						
Weight	2.5Kg																						
Configuration	AC Adapter,2Substrate Vtensil ,Instruction Manual ,Inspection report, Warranty Card																						